## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark:	vidaxl
--------------------------------	--------

**Supplier's address:** vidaXL, Mary Kingsleystraat 1 5928SK Venlo The Netherlands

Model identifier: 1003LRY01

_		•	•••				
٠.	ma	at I	$-\alpha$	nt	$c \sim$		~~:
	/pe	UI I	וצו		SU	uı	·-
- 7	, , , ,		· · O ·			••••	

Product parameters				
Anti-glare shield:	No	Dimmable:	No	
High luminance light source:	No			
Colour-tuneable light source:	No	Envelope:	-	
Mains or non-mains:	NMLS	Connected light source (CLS):	No	
Light source cap-type (or other electric interface)	-			
Lighting technology used:	LED	Non-directional or directional:	NDLS	
Lieletia este elemente en como ele	LED	Nam discretional as	NDLC	

Troduct parameters					
Parameter		Value	Parameter	Value	
	General product parameters:				
Energy consur mode (kWh/10 up to the neare	00 h), rounded	5	Energy efficiency class	G	
dicating if it refe a sphere (360º)	s flux (φuse), in- ers to the flux in , in a wide cone rrow cone (90º)	420 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	6 500	
On-mode power (P <sub>on</sub> ), expressed in W		5,0	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the sec- ond decimal	0,00	
Networked standby power (P <sub>net</sub> ) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	80	
Outer dimen-	Height	-	Spectral power dis-	See image	
sions without	Width	-	tribution in the	in last page	
separate con- trol gear, light- ing control	Depth	-	range 250 nm to 800 nm, at full-load		

parts and non- lighting con- trol parts, if any (millime- tre)					
Claim of equivalent power <sup>(a)</sup>	-	If yes, equivalent power (W)	-		
		Chromaticity coordi-	0,314		
		nates (x and y)	0,328		
Parameters for LED and OLED light sources:					
R9 colour rendering index value	5	Survival factor	0,90		
the lumen maintenance factor	0,96				

(a)'-': not applicable; (b)'-': not applicable;

